

PRODUCT DESCRIPTION

- Can create a line of light
- After mounting aluminum flanges are concealed

FINISH :

Non anodized (raw)

Fill empty fields

Product nr.	
Fixture type	
Company	
Job name	
Date	

TECHNICAL SPECIFICATION

Application

- for creating lines of light flush with the surface of walls and ceilings

Assembly

- fixed in the groove with fixing glue
- profile fastening wings covered with gypsum plaster
- The PROTECTIVE INSERT TECH-22 ensures that the profile slot remains wide enough for the snap-in cover (its use is NECESSARY during mounting and finishing works)

Additional information

- a TECH-22 protective insert that protects the inside of the profile during mounting is available


AVAILABLE LENGTHS

Ref. nr.	surface finish	available lengths
B6454NA_1	Non anodized (raw)	1000 mm
B6454NA_2	Non anodized (raw)	2000 mm
B6454NA_3	Non anodized (raw)	3000 mm





TECHNICAL DRAWING





RELATED PRODUCTS

COVERS



LIGER-22 black Cover Ref: 17044



MUN-22 semitransparent Cover Ref: 17042 **60°**



0


G-L frosted Cover Ref: 00413



G-K semi-transparent Cover Ref: 00415

LIGER-22 frosted Cover Ref: 17032V1 **110°**

HS-22 frosted Cover Ref: 17011 **100°**



sted HS-22 1 Ref: 1



G-L clear Cover

U

G-L semitransparent Cover Ref: 17008



G-K frosted Cover Ref: 17007

END CAPS



KOZEL grey End cap Ref: 24034

ACCESSORIES





TECH-22 protective insert Ref: 17124





L135 LIPOD

Coupler

L90 LIPOD Coupler Ref: Kształtka L90





L90PW LIPOD

ZM-NA-120 Connector Ref: 42729



.....

ZM-NA-135

Connector

Ref: 42725

ZM-NA-PION-135 Connector Ref: 42727



MARKETING MATERIALS



Display P230-90119M Ref: 90119M



Presentation set 2 Ref: 90052



L135PW LIPOD Coupler Ref: Kształtka L135PW



L90PZ LIPOD Coupler Ref: Kształtka L90PZ

ZM-NA-180

Connector

Ref: 42724



4

T135L LIPOD

L135PZ LIPOD

Ref: Kształtka L135PZ

Coupler

ZM-N Conne Ref: 4

ZM-NA-90 Connector Ref: 42723